
Y-Ball Bearings With Grub Screw Locking

UE 203-010 2S

Y-Ball Bearings With Grub Screw Locking








Technical Specification

d	Bore diameter	15.875	mm
d	Bore diameter	5/8	inch
D	Outside diameter	40	mm
B	Width inner ring	22.1	mm
C	Width outer ring	12	mm
s	Distance from inner ring side face to raceway centre	6.2	mm
d1	Outer diameter inner ring	24.2	mm
E	Distance from raceway centre to the hole for lubrication	3.6	mm
Gs	Set screw	10-32 UNF	inch
sw	Hexagonal key size for set screw	2.381	mm
r1,2	Inner ring Chamfer dimension	0.3	mm
r3,4	Outside ring Chamfer dimension	0.4	mm
Cdyn	Dynamic load rating	9.56	kN
Co	Static load rating	4.75	kN
Pu	Fatigue load limit	0.2	kN
kg	Mass	0.1	kg

Sealing

S SEAL / S SEAL (2S)



Single lip seal with the labyrinth between the sheet part and the rubber lip which conducts the contact sealing. The friction and speeds are the same as with RS but provides much better protection against the rough impurity particles. This is very good sealing system: the sheet part protects the seal from the soil, dust and rough particles. At the same time makes the labyrinth with the rubber part. The rubber part provides contact sealing which prevents penetration of finer impurities, water, moisture, steam etc. Suitable for neutral conditions because of the presence of the foreign materials. It is used with the Y bearing (standard) and deep groove ball bearings.