



# Y-Ball Bearings With Eccentric Locking Collar

## UY 203 2S.H

Y-Ball Bearings With Eccentric Locking Collar



### Technical Specification

d	Bore diameter	17 mm
D	Outside diameter	40 mm
B	Width inner ring	19.1 mm
C	Width outer ring	12 mm
s	Distance from inner ring side face to raceway centre	6.5 mm
d1	Outer diameter inner ring	24.2 mm
Gs	Set screw	M6x0.75 mm
sw	Hexagonal key size for set screw	3 mm
r1,2	Inner ring Chamfer dimension	0.3 mm
r3,4	Outside ring Chamfer dimension	0.4 mm
B1	Width inner ring with locking collar	28.6 mm
d2	Locking collar outside diameter	28.6 mm
B2	Width locking collar	13.5 mm
Cdyn	Dynamic load rating	9.55 kN
Co	Static load rating	4.75 kN
Pu	Fatigue load limit	0.2 kN
kg	Mass	0.11 kg

## Sealing

---

### S SEAL / S SEAL (2S)

Single lip seal with the labyrinth between the sheet part and the rubber lip which conducts the contact sealing. The friction and speeds are the same as with RS but provides much better protection against the rough impurity particles. This is very good sealing system: the sheet part protects the seal from the soil, dust and rough particles. At the same time makes the labyrinth with the rubber part. The rubber part provides contact sealing which prevents penetration of finer impurities, water, moisture, steam etc. Suitable for neutral conditions because of the presence of the foreign materials. It is used with the Y bearing (standard) and deep groove ball bearings.

